# Inspect

### **3D** Inline-Metrology





## Large FOV Industrial WLI

For applications where conventional sensors reach their limits, the heliInspect™ H9 and H9M excel with true sub-micrometer height resolution. The unmatched performance of these industry grade White-Light-Interferometers are based on Heliotis next generation 3D-pixel sensor heliSens<sup>™</sup> S4 and S4M.

#### Measurement capability extended

- Height measurements with true submicrometer accuracy
- Unprecedented measurement speed
- Higher resolution in x, y at given FOV
- Highest intra-scene dynamic range
- Large set of optical magnifications

#### Integration as easy as a 2D camera

- Standard Gen<i>CAM interface
- On-camera services for standard tasks

19MDSOD0



## Specifications for H9 / H9M



heliInspect™ H9-M	Key Features				
Measurement principle	White-Light Interferometer (industrial grade WLI)				
Sensor	Heliotis lock-in imager <mark>heli</mark> Sens™ S4∕S4M, in-pixel signal processing				
Camera board	FPGA based high-speed board, SOC, Linux OS, high-level interface through embedded heliService™				
Light source	High-power LED, $\lambda_c = 630 \text{ nm}$				
Scanner	Linear motor, precision guides, stroke = 40 mm or 80 mm, standard resolution = 100 nm				
Interfaces	Gen <i>Cam / GigE, GlO, power (24V)</i>				
Software	heliSDK™ for C++, C#, Halcon, Matrox, LabVIEW, Python				

Configuration	Зх	2 x	1.5 x	1 x	0.8 x	0.5 x
Field of view [mm <sup>2</sup> ]	4.10 x 4.35	6.14 x 6.53	8.19 x 8.70	12.29 x 13.06	15.36 x 16.32	24.58 x 26.11
Optical resolution H9	8	12	16	24	30	48
[µm] H9M	4	6	8	12	15	24
Working distance [mm] Standard Long WD	49 n. a.	49 110	51 n. a.	51 113	51 113	51 113
Numerical aperture Standard Long WD	0.15 n. a.	0.13 0.11	0.10 n. a.	0.067 0.067	0.053 0.053	0.033 0.033



For more information please contact sales@heliotis.ch Heliotis AG|Längenbold 5|CH-6037 Root / Lucerne| Switzerland